





°C	27	36	<u> </u>
Data Storage: Security Aware Appliance:  Manufacturer Reference (16 Bits) Manufacturer's Equipment Reference (48 Bits)	Electronic Serial Number (64 Bits) Appliance Location Code (ROC Identity 24 Bits, House Identity 40 Bits)	House Unlock Code (24 Bits) Appliance Unlock Code (24 Bits)	Blanking Code (24 Bits) Flags: Blanked, System Lock,

Fig 2









## TOSISSI ... ISSIST


Data Storage: Remote Operations Centre	Per Customer Location: Location Code (40 Bits)	House Unlock Code (24 Bits)	Identity (Customer Telephone Number, GPS, Unit ID, GSM_SIM)	Customer blanking PIN	Customer Name (20 ASCII Characters)	Customer Address (20 ASCII Characters) (Several Lines)	Number of Appliances in List (16 Bits)	Per Appliance: List No (16 Bits)	Equipment Type (64 Bits)	Electronic Serial Number (64 Bits)	Appliance Unlock Code (24 Bits)	Blanking Code (24 Bits)	Flags: Blank, System Lock,
--	--	-----------------------------	---	-----------------------	-------------------------------------	--	--	----------------------------------	--------------------------	------------------------------------	---------------------------------	-------------------------	----------------------------

Fig (


## 7/24


Data Storage: Home Control Centre (Volatile)	Number of Appliances in List (16 Bits)	House Unlock Code (24 Bits)	(Per Appliance): List No (16 Bits),	Appliance ID (128 Bits)	Appliance Unlock Code (24 Bits)	Blanking Code (24 Bits)	Flags: Blanked, System Lock,
--	--	-----------------------------	-------------------------------------	-------------------------	---------------------------------	-------------------------	------------------------------


8/24





9/24 \Down Power 409 009 Set System Lock Armed Blanking Code Fields 403 Store Unlock and Lock Enable System Lock Armed? System Power System Lock Z Enabled ,407 408 402 Unlock Code Response 400 Compare Unlock Correct Power Code Down, Fig 8A Wait Unlock Response 009 Power' Down, Power 500 ,414 009 Timer Expired 401 \ Unlock Hold Z Armed? System Lock 415 Power UpBlanking Code Fields Reset System Lock Blank Unlock & System Lock 500 Power 406. Disabled 412  $\succ$ Blanking Code Compare Instruction Correct Power Down, Code Z Blank 900

















OSSASST OSSOL

## 15/24




Fig 15

16/24






Fig 1





19/24








Fig 21


20/24











## 24/24

Data Storage: Stand Alone Home control
Number of Appliances in List (16 Bits)
House Unlock Code (24 Bits)
(Per Appliance): List No (16 Bits),
Appliance ID (128 Bits)
Appliance Unlock Code (24 Bits)
Blanking Code (24 Bits)
Flags: System Lock,

Fig 27